

ACH

TECHNICAL SPECIFICATIONS

love it! magazine is printed according to ISO 12647-4 in the process Standard Rotogravure. You will achieve the best results if you supply data and any proofs in the European Rotogravure Standard Version2.

All images should be supplied CMYK and using the *PSR_LWC_STD_V2_PT.icc* profile.

You can download this profile from ECI.ORG using the following link...

http://www.eci.org/lib/exe/fetch.php?id=de%3Adownloads&cache=cache&media=downloads:icc_profiles_from_eci:eci_gravure_psr_v2_2009.zip

DATA FORMATS

File type: PDF/X-4 or PDF/X1a (supplied in single pages)

Images Resolution : Colour and Greyscale should be 300dpi. Bitmap/Monochrome should be 1200dpi

Images Colour: Loss-free compression CMYK using the above mentioned icc profile

Fonts : All embedded (No multiple master, pseudo italics or bold)

Artwork Colour : All CMYK. No spot colours.

ADVERTISEMENT SPECIFICATIONS

Dimensions (for cover and body)

Page Type Area: 266 x 185mm

DPS Type Area: 266 x 390mm

Page Bleed: 296 x 210mm

DPS Bleed: 296 x 420mm

Page Trim: 286 x 205mm

DPS Trim: 285 x 410mm

Vertical Half Page Type Area: 266 x 90mm

Vertical Half Page Bleed: 296 x 105mm (Trim 286 x 100mm)

Horizontal Half Page Type Area: 129 x 185mm

Horizontal: Half Page Bleed: 144 x 210mm(Trim 139 x 205mm)

Quarter Page Box: 129 x 90mm

Delivery via email to: ads@loveit-magazine.co.uk